



WATER HEATING **PRODUCT GUIDE**



RELY ON RUUD.™

RESIDENTIAL HEAT PUMP



ULTRA HYBRID ELECTRIC HEAT PUMP WITH TOP WATER CONNECTIONS & LEAKGUARD™

- Meets NEEA Tier 4 requirements
- LeakGuard™ Integrated Leak Detection and Prevention System
- Title 24 Compliant (IA13 Ready) Demand Response Ready – Built-in EcoPort™ (CTA-2045 Port) allows easy connection to Utility programs
- 5 Smart Operating Modes
- Built-in Wi-Fi powered by EcoNet®
- 37-145° F Ambient operating temp. range
- 40, 50, 65 and 80-Gallon capacities
- 208-240 Volt, 1PH, 30 Amps

Limited Warranty

- Tank and Parts – 10 Years



ULTRA HYBRID ELECTRIC HEAT PUMP WITH TOP WATER CONNECTIONS

- Meets NEEA Tier 4 requirements
- Built-in Wi-Fi powered by EcoNet®
- 37-145° F Ambient operating temp. range
- LeakGuard™ and LeakSense™ Ready – Easily add leak detection and prevention with leak sensor and shutoff valve
- Title 24 Compliant (IA13 Ready) Demand Response Ready – Built-in EcoPort™ (CTA-2045 Port) allows easy connection to Utility programs
- 5 Smart Operating Modes
- 40, 50, 65 and 80-Gallon capacities
- 208-240 Volt, 1PH
- 15 and 30 Amp models

Limited Warranty

- Tank and Parts – 10 Years



ULTRA PLUG-IN HEAT PUMP (120V DEDICATED CIRCUIT)

- Up to 3.0 UEF reduces operating cost
- LeakGuard™ and LeakSense™ Ready – Easily add leak detection and prevention with leak sensor and shutoff valve upgrade kit
- Title 24 Compliant (IA13 Ready) Demand Response Ready – Built-in EcoPort™ (CTA-2045 Port) allows easy connection to Utility programs
- Built-in Wi-Fi powered by EcoNet®
- 37-145° F Ambient operating temp. range
- 40, 50, 65 and 80-Gallon capacities

Limited Warranty

- Tank and Parts – 10 Years



ULTRA PLUG-IN HEAT PUMP WITH HYDROBOOST AND LEAK GUARD™ (120V SHARED CIRCUIT)

- Up to 3.46 UEF reduces operating cost
- Title 24 Compliant (IA13 Ready) Demand Response Ready – Built-in EcoPort™ (CTA-2045 Port) allows easy connection to Utility programs
- LeakGuard™ Integrated leak detection and prevention system with factory installed auto water shut-off valve
- Built-in Wi-Fi powered by EcoNet®
- 37-145° F Ambient operating temp. range
- 40, 50, 65 and 80-Gallon capacities

Limited Warranty

- Tank and Parts – 10 Years

Heat Pump Continued



ULTRA PLUG-IN HEAT PUMP WITH HYDROBOOST (120V SHARED CIRCUIT)

- Up to 3.46 UEF reduces operating cost
- Title 24 Compliant (IA13 Ready) Demand Response Ready – Built-in EcoPort™ (CTA-2045 Port) allows easy connection to Utility programs
- Built-in Wi-Fi powered by EcoNet®
- 37-145° F Ambient operating temp. range
- 40, 50, 65 and 80-Gallon capacities

Limited Warranty

- Tank and Parts – 10 Years

TANKLESS GAS



SR-SERIES SUPER HIGH EFFICIENCY CONDENSING TANKLESS GAS

- .96 UEF
- Single indoor/outdoor unit meets almost any installation need (Outdoor conversion kit sold separately)
- Built-in Recirculation pump for instant hot water at the tap (SR-Series)
- Field gas convertible from natural gas to LP – conversion kit included
- PVC Vent runs up to 70' (2"), 150' (3")
- Up to 11.2 gal./min. @ 35° F rise
- Up to 8.8 gal./min. @ 45° F rise
- 11,000 - 199,900 BTU/h max.

Limited Warranty

- Heat Exchanger – 15 Years
- Parts – 5 Years
- Labor – 1 Year



RUTGH SERIES SUPER HIGH EFFICIENCY CONDENSING

- Up to .93 UEF
- Single indoor/outdoor unit meets almost any installation need (Outdoor conversion kit sold separately)
- Ultra Low NOx natural gas and LP models
- 9.5 gal./min. at 35° F rise
- 8.5 gal./min. at 45° F rise
- 11,000 - 199,900 BTU/h max.

Limited Warranty

- Heat Exchanger – 15 Years
- Parts – 5 Years
- In-Home Labor – 1 Year



RUTG SERIES HIGH EFFICIENCY NON-CONDENSING

- Up to .82 UEF
- Indoor direct vent and outdoor models
- Ultra Low NOx natural gas and LP models
- 9.5 gal./min. at 35° F rise
- 7.4 gal./min. at 45° F rise
- 11,000 - 199,900 BTU/h max.

Limited Warranty

- Heat Exchanger – 15 Years
- Parts – 5 Years
- Labor – 1 Year

L-SERIES WHOLE HOME HEATING SOLUTION



L-SERIES SUPER HIGH EFFICIENCY TANKLESS GAS WATER HEATER

- .90 UEF
- Innovative Labyrinth Heat Exchanger with 2 independent copper waterways for maximum heat transfer and minimal heat loss
- Indoor direct vent models
- Field gas convertible from natural gas to LP
- 10.1 gal./min. at 35° F rise
- 7.9 gal./min. at 45° F rise
- 28,500 - 199,000 BTU/h max.

Limited Warranty

- Heat Exchanger – 15 Years
- Parts – 5 Years
- In-Home Labor – 1 Year



L-SERIES COMBINATION BOILER

- Up to 95% AFUE
- Innovative Labyrinth Heat Exchanger with 2 independent copper waterways for maximum heat transfer and minimal heat loss
- Built-in ECM variable speed, high efficiency boiler pump
- Built-in Illuminated Touchscreen Control Panel
- 28,500 - 199,000 BTU/h max.

Limited Warranty

- Heat Exchanger – 10 Years
- Parts – 5 Years
- Labor – 1 Year



L-SERIES BOILER

- Up to 96% AFUE
- Innovative Labyrinth Heat Exchanger with 2 independent copper waterways for maximum heat transfer and minimal heat loss
- Built-in ECM variable speed, high efficiency boiler pump
- Built-in Illuminated Touchscreen Control Panel
- 13,650 - 120,000 BTU/h max.

Limited Warranty

- Heat Exchanger – 10 Years
- Parts – 5 Years
- Labor – 1 Year



ULTRA SUPER HIGH EFFICIENCY WITH LEAKSENSE™

- Up to 3.8 GPM continuous flow of hot water at setpoint temperature
- Highest Delivery of 192 gallons in MaxMode™
- Built-in Wi-Fi powered by EcoNet®
- LeakSense™ built-in leak detection system detects any leak, internal or external
- 40 and 50-Gallon capacities
- Up to 76,000 BTU/h

Limited Warranty

- Tank and Parts – 12 Years



ULTRA SUPER HIGH EFFICIENCY HEAVY DUTY WITH LEAKSENSE™

- Up to 3.8 GPM continuous flow of hot water at setpoint temperature
- Highest Delivery of 198 gallons in MaxMode™
- Built-in Wi-Fi powered by EcoNet®
- LeakSense™ built-in leak detection system detects any leak, internal or external
- 75-Gallon capacity
- Up to 100,000 BTU/h

Limited Warranty

- Tank and Parts – 12 Years



ACHIEVER SUPER HIGH EFFICIENCY

- Up to .90 UEF reduces operating cost
- Built-in Condensate Neutralizer
- Side water connections for space heating applications
- Easy to use LCD display with integrated diagnostics
- 40 and 50-Gallon capacities
- Up to 50,000 BTU/h

Limited Warranty

- Tank and Parts – 8 Years



ULTRA POWERED DAMPER

- .68 - .69 UEF
- Energy efficient damper design
- Integrated self-diagnostic system control, flammable vapor detection sensor
- 38 and 50-Gallon capacities
- Up to 40,000 BTU/h

Limited Warranty

- Tank and Parts – 12 Years

Residential Tank-Type Gas Continued



ACHIEVER PLUS INDUCED DRAFT

- .71 UEF
- Recovery rate: 61 GPH at a 90° F rise
- 29 Gallon capacity with 93-Gallon FHR performance
- Small foot print, 17-3/4 inch diameter
- 60,000 BTU/h, nat. gas only

Limited Warranty

- Tank and Parts – 8 Years



ACHIEVER PLUS POWERED DAMPER

- .65 - .69 UEF
- Recovery rate: 36.4 to 50.5 GPH at a 90° F rise
- Energy efficient 24 VAC flue damper
- Meets 40 ng/J NOx requirements
- 38, 40, and 50-Gallon capacities
- Up to 50,000 BTU/h

Limited Warranty

- Tank and Parts – 8 Years



ACHIEVER PLUS ATMOSPHERIC

- .58 - .66 UEF
- Recovery rate: 36.4 to 61 GPH at a 90° F rise
- Side water connections available on select models
- Meets 40 ng/J NOx requirements
- 40, 48, 50 and 55-Gallon capacities
- Up to 60,000 BTU/h

Limited Warranty

- Tank and Parts – 8 Years



ACHIEVER PLUS HEAVY DUTY ATMOSPHERIC

- Recovery capacity: 72.8 GPH at a 100° F rise
- Meets 40 ng/J NOx requirements
- 75 and 98-Gallon capacities
- 75,100 BTU/h

Limited Warranty

- Tank and Parts – 8 Years

Residential Tank-Type Gas Continued



ACHIEVER PLUS POWER DIRECT VENT

- .65 UEF
- Recovery rate: 47.5 to 65.7 GPH at a 90° F rise
- Long venting options up to 100 ft.
- Meets 40 ng/J NOx requirements
- 50-Gallon capacity
- Up to 65,000 BTU/h

Limited Warranty

- Tank and Parts – 8 Years



ACHIEVER PLUS HEAVY DUTY POWER DIRECT VENT

- Recovery capacity: 72.8 GPH at a 100° F rise
- Long venting options up to 100 ft.
- Meets 40 ng/J NOx requirements
- 75-Gallon capacity
- 75,100 BTU/h

Limited Warranty

- Tank and Parts – 8 Years



ACHIEVER PLUS HEAVY DUTY POWER VENT

- Recovery capacity: 72.8 GPH at a 100° F rise
- Long venting options up to 100 feet
- Integrated self-diagnostic system
- 75-Gallon capacity
- 75,100 BTU/h

Limited Warranty

- Tank and Parts – 8 Years



ACHIEVER ATMOSPHERIC

- .58 - .66 UEF
- Recovery rate: 30.3 to 40.4 GPH at a 90° F rise, based on model
- Features the Guardian System
- Meets 40 ng/J NOx requirements
- Factory installed top T&P valve and side water connections available on select models
- 29, 30, 40 and 50-Gallon capacities
- Up to 60,000 BTU/h

Limited Warranty

- Tank and Parts – 6 Years

Residential Tank-Type Gas Continued



ACHIEVER POWER VENT

- .65 - .70 UEF
- Recovery rate: 32.4 to 42.4 GPH at a 90° F rise, based on model
- Long venting options up to 150 feet
- Whisper quiet blower
- Side water connections available on select models
- 40 and 50-Gallon capacities
- Up to 42,000 BTU/h

Limited Warranty

- Tank and Parts – 6 Years



ACHIEVER POWER DIRECT VENT

- .63 - .69 UEF
- Recovery rate: 38.4 to 40.4 GPH at a 90° F rise, based on model
- Long venting options up to 100 feet
- Whisper quiet blower
- 40 and 50-Gallon capacities
- Up to 40,000 BTU/h

Limited Warranty

- Tank and Parts – 6 Years



ACHIEVER DIRECT VENT

- .56 - .61 UEF
- Recovery rate: 30.3 to 36.4 GPH at a 90° F rise
- Adjustable coaxial vent
- Longer venting options
- 40 and 50-Gallon capacities
- Up to 36,000 BTU/h

Limited Warranty

- Tank and Parts – 6 Years



CLASSIC ATMOSPHERIC FOR MANUFACTURED HOUSING

- .59 - .60 UEF
- Recovery rate: 30.3 to 34.3 GPH at a 90° F rise, based on model
- CSA and HUD certified
- Features the Guardian System
- 29 and 40-Gallon capacities
- Up to 34,000 BTU/h

Limited Warranty

- Tank and Parts – 6 Years

Residential Tank-Type Gas Continued



CLASSIC DIRECT VENT FOR MANUFACTURED HOUSING

- .57 - .59 UEF
- Recovery rate: 30.3 GPH at a 90° F rise
- CSA and HUD certified
- Combustion air comes from outside
- 30 and 40-Gallon capacities
- Up to 30,000 BTU/h

Limited Warranty

- Tank and Parts – 6 Years



CLASSIC DIRECT VENT CO-AXIAL FOR MANUFACTURED HOUSING

- .63 - .65 UEF
- Recovery rate: 30.3 to 36.4 GPH at a 90° F rise, based on model
- CSA and HUD certified
- 40 and 50-Gallon capacities
- Up to 36,000 BTU/h

Limited Warranty

- Tank and Parts – 6 Years



ULTRA POWERED DAMPER ULTRA LOW NOx

- .64 - .68 UEF
- Energy efficient damper design
- Integrated self-diagnostic system control, flammable vapor detection sensor
- 40 and 50-Gallon capacities
- Ultra low NOx 38,000 BTU/h burner

Limited Warranty

- Tank and Parts – 12 Years



ACHIEVER PLUS POWERED DAMPER ULTRA LOW NOx

- .64 - .68 UEF
- Recovery rate: 38 GPH at a 90° F rise
- Energy efficient 24 VAC flue damper
- Meets 10 ng/J NOx requirements
- 40 and 50-Gallon capacities
- Ultra low NOx 38,000 BTU/h burner

Limited Warranty

- Tank and Parts – 8 Years

Ultra Low NOx Continued



ACHIEVER PLUS ULTRA LOW NOx

- .58 - .64 UEF
- Recovery rate: 30 to 45 GPH at a 90° F rise, based on model
- Features the Guardian System
- Meets 10 ng/J NOx requirements
- Factory installed top T&P valve available on select models
- 29, 40, 50 and 55-Gallon capacities
- Up to 45,000 BTU/h

Limited Warranty

- Tank and Parts – 8 Years



ACHIEVER PLUS HEAVY DUTY ULTRA LOW NOx

- Recovery capacity: 72.8 - 77.6 GPH at a 90° F rise
- Meets 14 ng/J NOx requirements
- Features flammable detection system
- 75 and 98-Gallon capacities
- Up to 80,000 BTU/h, natural gas only

Limited Warranty

- Tank and Parts – 8 Years



ACHIEVER ULTRA LOW NOx

- .58 - .64 UEF
- Recovery rate: 30 to 38 GPH at a 90° F rise, based on model
- Meets 10 ng/J NOx requirements
- Features the Guardian System
- Factory installed top T&P valve and side water connections available on select models
- High BTU/h and skinny models available
- 29, 39, 40 and 50-Gallon capacities
- Up to 48,000 BTU/h

Limited Warranty

- Tank and Parts – 6 Years



ACHIEVER HEAVY DUTY ULTRA LOW NOx

- Recovery: 72.8 GPH at a 90° F rise
- Meets 14 ng/J NOx requirements
- Features the Guardian System
- 75 and 98-Gallon capacities
- 75,100 BTU/h

Limited Warranty

- Tank and Parts – 6 Years

Ultra Low NOx Continued



ACHIEVER POWER VENT ULTRA LOW NOx

- .64 - .68 UEF
- Recovery rate: 36.4 to 38.4 GPH at a 90° F rise, based on model
- Long venting options up to 100 feet
- Whisper quiet blower
- 40 and 50-Gallon capacities
- Up to 38,000 BTU/h

Limited Warranty

- Tank and Parts – 6 Years



ULTRA SMART ELECTRIC WITH LEAKGUARD™

- .92 - .93 UEF
- Recovery rate: 25 GPH at a 90° F rise
- Dual 5500 watt stainless steel heating elements
- LeakGuard™ Integrated Leak Detection and Prevention System with factory installed auto water shut-off valve
- LeakSense™ Built-in Leak Detection System detects any leak large or small
- Built-in Wi-Fi powered by EcoNet®
- 40, 50 and 55-Gallon capacities

Limited Warranty

- Tank and Parts – 12 Years



ULTRA SMART ELECTRIC WITH LEAKGUARD™ AND DEMAND RESPONSE

- .92 - .93 UEF
- Recovery rate: 21-25 GPH at a 90° F rise
- Demand response ready EcoPort™ (CTA-2045 port) is built in for easy connect to utility demand response programs
- LeakGuard™ Integrated Leak Detection and Prevention System with factory installed auto water shut-off valve
- Built-in Wi-Fi powered by EcoNet®
- 40, 50 and 55-Gallon capacities

Limited Warranty

- Tank and Parts – 12 Years



ACHIEVER PLUS SMART ELECTRIC WITH LEAKSENSE™

- .92 - .93 UEF
- Recovery rate: 21 GPH at a 90° F rise
- Dual 4500 watt stainless steel heating elements
- LeakSense™ Built-in Leak Detection System detects any leak large or small
- Built-in Wi-Fi powered by EcoNet®
- 40, 50 and 55-Gallon capacities

Limited Warranty

- Tank and Parts – 8 Years

RESIDENTIAL TANK-TYPE ELECTRIC | Professional Ultra™, Achiever Plus® & Achiever® Models

Residential Tank-Type Electric Continued



ACHIEVER PLUS SMART ELECTRIC WITH LEAKSENSE™ AND DEMAND RESPONSE

- .92 - .93 UEF
- Recovery rate: 21-25 GPH at a 90° F rise
- Demand response ready EcoPort™ (CTA-2045 port) is built in for easy connect to utility demand response programs
- Dual 4500 or 5500 watt SS heating elements
- LeakSense™ Built-in Leak Detection System detects any leak large or small
- Built-in Wi-Fi powered by EcoNet®
- 40, 50 and 55-Gallon capacities
- 240 Volt AC/Single phase

Limited Warranty

- Tank and Parts – 8 Years



ACHIEVER

- .90 - .93 UEF
- Recovery rate: 21 GPH at a 90° F rise
- Restored stainless steel lower heating element
- 19.9 to 55-Gallon capacities
- 240 Volt AC/Single phase

Limited Warranty

- Tank and Parts – 6 Years



ACHIEVER ELECTRIC WITH DEMAND RESPONSE

- .92 - .93 UEF
- Recovery rate: 17-21 GPH at a 90° F rise
- Demand response ready EcoPort™ (CTA-2045 port) is built in for easy connect to utility demand response programs
- Dual 4500 or 5500 watt copper heating elements
- 40, 50 and 55-Gallon capacities
- 240 Volt AC/Single phase

Limited Warranty

- Tank and Parts – 6 Years



ACHIEVER POINT-OF-USE

- .90 UEF for 30-Gallon model
- Space-saving design for installation in limited spaces
- Single restored stainless steel heating element
- Automatic thermostat and over-temperature protector
- 2.5, 6, 10, 15, 20 and 30-Gallon capacities

Limited Warranty

- Tank and Parts – 6 Years

**ACHIEVER SHORT (LOWBOY) WITH SIDE WATER CONNECTIONS**

- .92 - .94 UEF
- Recovery rate: Up to 28 GPH at a 90° F rise depending on model
- Restored stainless steel upper and lower heating elements
- Models are compliant to HUD Standards for manufactured housing and modular construction
- 28 and 38-Gallon capacities

Limited Warranty

- Tank and Parts – 6 Years

**CLASSIC FOR MANUFACTURED HOUSING**

- .92 - .93 UEF
- Recovery rate: 17 to 21 GPH at a 90° F rise
- CSA and HUD certified
- Restored stainless steel upper heating element
- 19.9, 30, 40 and 50-Gallon capacities
- 240 volt AC/Single phase

Limited Warranty

- Tank and Parts – 6 Years

**TABLE TOP**

- .81 UEF
- Recovery rate: 21 GPH at a 90° F rise
- Designed for areas that require additional counter space
- Baked enamel counter top is acid and heat resistant
- 40-Gallon capacity
- 240 Volt AC/Single phase

Limited Warranty

- Tank and Parts – 6 Years

**CLASSIC TANKLESS ELECTRIC**

- Up to .96 UEF
- No venting required
- Ideal for point-of-use or whole home applications
- Saves space- compact & stylish
- Thermostatic digital temperature control
- Advanced self modulation technology
- Mounts vertically
- Nine models available - 3.5 kW to 36 kW

Limited Warranty

- Heating Chamber – 5 Years
- Parts – 1 Year

MARATHON®

**MARATHON®**

- .88 - .92 UEF
- Recovery rate: up to 21 GPH at a 90° F rise
- Seamless, polybutene tank
- Light weight and easy to install
- 30 to 105-Gallon capacities
- 240 Volt AC/Single phase

Limited Warranty

- Tank – Limited Lifetime*
- Parts – 6 Years

**MARATHON® POINT-OF-USE**

- Ideal for condos, cabins and light-duty commercial applications
- Seamless, polybutene tank
- 15 and 19.9-Gallon capacities
- 120 and 240 Volt AC
- 2 kW and 3 kW elements

Limited Warranty

- Tank – Limited Lifetime*
- Parts – 6 Years

*Warranty is provided to original customer in a residential application after online product registration is complete. Registration must be completed within 90 days of installation. See Warranty Certificate for complete information.

Solar Continued

SOLAR

**SOLPAK™ ACTIVE SYSTEM WITH ELECTRIC BACKUP**

- HE Storage tank, collectors & pump station
- Collectors OG-100 certified by SRCC
- Pump station includes 3 speed pump, controller, balancing valve and flow meter
- System OG-300 certified by SRCC
- 65, 80 and 120-Gallon capacities; collectors available in 3 sizes

Limited Warranty

- Tank – 6 Years
- Collector – 10 Years
- Pump Station – 6 Years

**SOLPAK™ ACTIVE SYSTEM WITH GAS BACKUP**

- HE Storage tank, collectors & pump station
- Collectors OG-100 SRCC certified
- Pump station includes 3 speed pump, controller, balancing valve and flow meter
- System OG-300 cert. by SRCC pending
- 75-Gallon capacity; collectors available in two sizes

Limited Warranty

- Tank – 6 Years
- Collector – 10 Years
- Pump Station – 6 Years

**SOLPAK™ PUMP MASTER**

- Complete package for closed loop glycol systems
- Includes cast iron 3 speed pump, differential controller and flow meter
- Compact insulated enclosure
- Pressure relief valve with pressure gauge and expansion tank connection

Limited Warranty

- 6 Years

**SOLAR COLLECTORS**

- OG-100 certified by SRCC
- Durable low iron tempered glass
- Integral mounting channel for easy installation
- Stainless steel fasteners
- Suitable for open and closed loop systems
- Copper absorber plate
- Can be mounted horizontally or vertically

Limited Warranty

- Collector – 10 Years

**SOLARAIDE® HE**

- Designed for use with closed loop solar systems
- Choice of two models – storage tank or single element water heater
- A special 1/2" NPT opening is provided for installation for a "probe-type" thermistor
- Double wall, wrap around heat exchanger
- 65, 80, 120-Gallon capacities

Limited Warranty

- Tank and Parts – 6 Years

**SOLARAIDE® HE WITH GAS ASSIST**

- For use in residential closed loop solar water heating applications
- Single tank solution
- Double wall, high efficient solar heat exchanger
- Fast recovery for high demand applications
- Front solar connections for easy installations
- 75-Gallon capacity
- 75,100 BTU/h

Limited Warranty

- Tank and Parts – 6 Years

Solar Continued

STORAGE TANKS

**SOLARAIDE® STORAGE**

- Choice of a high efficiency 4500 Watt backup electric water heater or a storage tank
- Multi-port connections - top and sides
- 80 and 120 Gallon capacities

Limited Warranty

- Tank and Parts – 6 Years

**MARATHON® THERMAL STORAGE TANKS**

- Specifically designed for alternative energy applications
- Large water connections for lower pressure drop
- Tank – impervious to rust, corrosion
- 50, 85 and 105-Gallon capacities, 2 port and 3 port configurations
- 240 Volt/Single Phase

Limited Warranty

- Tank – Lifetime
- Parts – 6 Years

**STORAGE TANKS**

- Designed for applications that need large quantities of hot water in a short period of time
- Long tank life
- Fits through a 30"-33" opening
- 2" rigid foam insulation
- 80, 115 and 175-Gallon capacities

Limited Warranty

- Tank – 5 Years

**LARGE VOLUME STORAGE TANKS**

- Porcelain enamel lined tank
- ASME certified
- Available in jacketed and non-jacketed models
- 200 to 950-Gallon capacities

Limited Warranty

- Tank – 5 Years

COMMERCIAL TANK-TYPE GAS



TRITON SUPER DUTY

- 95% Thermal efficiency
- Base SU model with LeakSense™
- Premium SS model: LeakGuard™ with auto shutoff valve and Integrated BMS Connectivity Via BACnet (MS/TP)
- Energy & water usage reports
- Faster, less costly venting – Polypropylene, PVC, CPVC, InnoFlue® Flex Vent and ABS materials; 3, 4 and 6 inch
- 119-Gallon capacity
- 499,900 BTU/h

Limited Warranty

- SS Models Tank – 5 Year
- SU Models Tank – 3 Year
- Parts – 1 Year



TRITON HEAVY DUTY

- Up to 98% Thermal efficiency
- Base SU model with LeakSense™
- Premium SS model: LeakGuard™ with auto shutoff valve and Integrated BMS Connectivity Via BACnet (MS/TP)
- Energy & water usage reports
- Faster, less costly venting – Polypropylene, PVC, CPVC, InnoFlue® Flex Vent and ABS materials; 2, 3, 4 and 6 inch
- 80 and 100-Gallon capacities
- 130,000 - 399,900 BTU/h

Limited Warranty

- SS Models Tank – 5 Year
- SU Models Tank – 3 Year
- Parts – 1 Year



TRITON LIGHT DUTY

- Up to 97% Thermal efficiency
- Base SU model with LeakSense™
- Premium SS model: LeakGuard™ with auto shutoff valve and Integrated BMS Connectivity Via BACnet (MS/TP)
- Faster, less costly venting – Polypropylene, PVC, CPVC, InnoFlue® Flex Vent and ABS materials; 2, 3, 4 and 6 inch
- Touch screen diagnostics system
- 50 and 75-Gallon capacities
- 76,000 - 100,000 BTU/h

Limited Warranty

- SS Models Tank – 5 Year
- SU Models Tank – 3 Year
- Parts – 1 Year



UNIVERSAL™

- 80% Thermal efficiency
- Designed to fit into tight retrofit applications – compact with multiple water connections
- Space-saving tank design
- System Sentinel™ LED diagnostics
- Multi-flue tank design
- 35 to 100-Gallon capacities
- 125,000 - 399,900 BTU/h

Limited Warranty

- Tank – 3 Years, upgradable to 5-years
- Parts – 1 Year

Commercial Tank-Type Gas Continued



UNIVERSAL™ LOW NOx

- 80% Thermal efficiency
- Designed to fit into retrofit applications
- System Sentinel™ LED diagnostics
- Low NOx burner meets 40 ng/J NOx requirements
- 35 to 100-Gallon capacities
- 125,000 - 399,900 BTU/h

Limited Warranty

- Tank – 3 Years, upgradable to 5-years
- Parts – 1 Year



UNIVERSAL™ ULTRA LOW NOx

- Up to 82% thermal efficiency
- Low NOx burner meets 14 ng/J NOx requirements
- Designed to fit in tight retrofit applications
- System sentinel LED diagnostics
- 35 to 100-Gallon capacities
- 125,000 to 399,900 BTU/h

Limited Warranty

- Tank – 3 Years, upgradable to 5-years
- Parts – 1 Year




XTREME™

- 80% Thermal efficiency
- Advanced line of fast recovery commercial water heaters – up to 756 GPH per hour at a 100° F rise
- Space-saving tank design
- 90-Gallon capacity
- High-input – 500,000 - 715,000 BTU/h

Limited Warranty

- Tank – 3 Years, upgradable to 5-years
- Parts – 1 Year



HOT WATER SUPPLY HEATERS

- 82% Thermal efficiency
- Indoor and outdoor installations
- Certified for a 160 PSI maximum working pressure
- 511,500 - 1,826,000 BTU/h

Limited Warranty

- Tank – 1 Year
- Parts – 1 Year
- Heat Exchanger – 5 Years

Commercial Tank-Type Gas Continued



MEDIUM-DUTY

- 80% Thermal efficiency
- Use where medium quantities of hot water are required
- Short floor-to-vent heights
- 48, 75, 98 and 100-Gallon capacities
- 54,000 - 80,000 BTU/h

Limited Warranty

- Tank – 3 Years, upgradable to 5-years
- Parts – 1 Year



MEDIUM DUTY ULTRA LOW NOx

- The tighter the commercial retrofit, the more you will appreciate how this water heater's compact size simplifies installations. Designed for maximum temperature settings of 180° F
- Side water connections for space heating applications
- 75 and 98 Gallon Capacities
- 75,100 BTU/h

Limited Warranty

- Tank – 3 Years, upgradable to 5-years
- Parts – 1 Year



POWER VENT

- 80% Thermal efficiency
- Use where medium quantities of hot water are required
- Uses 3" or 4" schedule 40 PVC, CPVC or ABS pipe
- Vents up to 95 feet
- 75-Gallon capacity
- 75,100 BTU/h

Limited Warranty

- Tank – 3 Years, upgradable to 5-years
- Parts – 1 Year



POWER DIRECT VENT

- 80% Thermal efficiency on 75-gallon models
- .62 EF on 50 gallon models
- Two pipe system: one pipe pulls in outside air for combustion; the other exhausts combustion gases
- Flammable vapor detection sensor
- 50 and 75-Gallon capacities
- 65,000 - 75,100 BTU/h

Limited Warranty

- Tank – 3 Years, upgradable to 5-years
- Parts – 1 Year

Commercial Tank-Type Gas Continued



POWER VENT KITS

- Use with natural gas or LP Universal models
- Use for vent lengths up to a maximum of 50 feet including the vent terminal
- Vent terminal can be installed through combustible or non-combustible surfaces – heat shield is provided
- Inputs: 98,000 - 400,000 BTU/h

COMMERCIAL TANK-TYPE ELECTRIC



LARGE VOLUME HIGH-POWER

- Vertical round, square and horizontal
- Glass lined tank
- 150 to 2,500-Gallon storage
- 208, 240, 277, 380, 415 and 600 voltages
- 144 kW - 900 kW

Limited Warranty

- Tank – 3 Years
- Parts – 1 Year



HEAVY DUTY

- Surface mounted and immersion thermostat models available
- System Sentinel™ LED diagnostics
- 50, 85, 120 and 175-Gallon capacities
- 208, 240, 277 and 480 voltages
- 12.3 kW - 108 kW

Limited Warranty

- Tank – 3 Years, upgradable to 5-years
- Parts – 1 Year
- Element – 3 Years



POWERPACK™

- System Sentinel™ LED diagnostics
- Minimal heat loss design
- Immersion thermostat
- Lifeguard™ stainless steel element
- ASME only
- 13, 19.9, 30 and 40-Gallon capacities
- 208, 240, 277 and 480 voltages
- Up to 36 kW

Limited Warranty

- Tank – 3 Years, upgradable to 5-years
- Parts – 1 Year
- Element – 3 Years



MARATHON® ECLIPSE™

- Terminal block available on 75, 85 and 105-gallon models – easily convert standard models from simultaneous to non-simultaneous, single phase to three phase
- Lightweight and easy to install
- 50, 75, 85 and 105-Gallon capacities

Limited Warranty

- Tank – 10 Years
- Parts – 1 Year

Commercial Tank-Type Electric Continued



ECLIPSE™

- 98% Thermal efficiency
- Polybutene tank – durable and lightweight
- No anode rod required
- 85 and 105-Gallon capacities
- 208, 240, 277 and 480 voltages, single or three phase
- Inputs from 12.4, 18 and 24 kW

Limited Warranty

- Tank – 10 Years
- Parts – 1 Year



LIGHT SERVICE

- Simultaneous wiring, single phase
- Patented resistor elements
- 2-1/2" of rigid polyurethane foam insulation
- Surface mounted thermostat automatically cycles on and off to maintain the water temperature at a desired preset level
- Factory installed brass drain valve
- 65, 80 and 119.9-Gallon capacities
- 12.1kW and in 277 voltage

Limited Warranty

- Tank – 6 Years
- Parts – 1 Year



LIGHT DUTY WITH TERMINAL BLOCK

- Easily convert standard models from simultaneous to non-simultaneous, single phase to three phase
- Porcelain enamel lined tank
- Automatic temperature control
- 30 to 119.9-Gallon capacities
- 208, 240, 277 and 480 voltages
- 3 kW - 12 kW

Limited Warranty

- Tank – 3 Years, upgradable to 5-years
- Parts – 1 Year



UL approved
electric conversion kits
available

POINT-OF-USE

- Designed to eliminate costly temperature loss in long piping runs
- Porcelain enamel lined tank
- Heavy duty anode rod
- 2.5, 6, 10, 15, 19.9 and 30-Gallon capacities
- 120, 208, 240, 277 and 480 volts
- 1440 - 6000 watts

Limited Warranty

- Tank – 3 Years, upgradable to 5-years
- Parts – 1 Year

Commercial Tank-Type Electric Continued



BOOSTER

- Designed to fit under counters and deliver sanitizing rinse for commercial dishwashers
- System Sentinel™ LED diagnostics
- Immersion thermostat
- Manual reset high limit control
- 6" stainless steel legs
- 208, 240, 277 and 480 voltages
- 6 kW - 54 kW

Limited Warranty

- Tank – 3 Years, upgradable to 5-years
- Parts – 1 Year



LIGHT DUTY HEAT PUMP

- Up to 4.0 UEF
- Meets Northern Climate Spec (Tier 4)
- Full-color LCD display
- 37-145° F Ambient operating temperature range
- Service notifications and water sensor alert with audible alarm
- 40, 50, 65 and 80-Gallon capacities
- 208-240 Volt, 1PH, 30 Amps

Limited Warranty

- Tank and Parts – 3 Years



HEAVY DUTY HEAT PUMP

- Delivers hot water with a system Coefficient of Performance (COP) exceeding 4.0 at 80°F ambient and 60% relative humidity.
- 135k BTU/h models are ENERGY STAR® certified
- 208 or 240 Volt / 1 PH or 480 Volt / 3 PH
- Flexible Indoor or Outdoor Use
- Double Wall Heat Exchanger

Limited Warranty

- 1-Year limited Warranty

COMMERCIAL TANKLESS ELECTRIC FOR HANDWASHING



THERMOSTATIC TANKLESS ELECTRIC WITH INTEGRATED MIXING VALVE

- Integrated mixing valve meets ASSE 1070
- Self-diagnostics with intelligent controls actively protect heater in installed environment
- SafeStart™ technology engages upon start-up to help avoid dry-fire occurrence
- Low flow activation at 0.3 GPM
- Digital LED display communicates system status and heater operation feedback

Limited Warranty

- 5-Year limited warranty on leaks
- Parts – 1 Year



THERMOSTATIC TANKLESS ELECTRIC

- Self-diagnostics with intelligent controls actively protect heater in installed environment
- SafeStart™ technology engages upon start-up to help avoid dry-fire occurrence
- Industry leading low flow activation at 0.2 GPM
- Digital LED display with accessible user interface communicates system status and heater operation feedback

Limited Warranty

- 5-Year limited warranty on leaks
- Parts – 1 Year



NON-THERMOSTATIC TANKLESS ELECTRIC

- Self-diagnostics with intelligent controls actively protect heater in installed environment
- InfoCue™ visible LED indicator communicates system status and heater operation feedback
- SafeStart™ technology engages upon start-up to help avoid dry-fire occurrence
- Low flow activation at 0.25 GPM (model dependent)

Limited Warranty

- 5-Year limited warranty on leaks
- Parts – 1 Year



Our comprehensive suite of high-efficiency products empowers you to drive a more sustainable future with zero trade-offs in value and comfort. Our water heaters are designed to improve your home's efficiency, achieve certifications such as ENERGY STAR® and qualify for tax credits and local rebates.



Ruud.com/water-incentives

Contact Us

Customer Service, Warranty, Parts **800.621.5622**
 Tankless Customer Service, Warranty, Parts..... **866.720.2076**
 Technical Service **800.HEATER3**
 (800.432.8373)
 Technical Service for Hybrid Water Heater **800.995.0982**
 EcoNet Support **800.255.2388**
 Fax **800.535.9538**
 Plumber Business Support **866.339.2388**
PlumberBusinessSupport@Ruud.com
 Website **Ruud.com**

PARTS AND ACCESSORIES

Ruud offers a wide assortment of parts and accessories for all your water heating needs. For more information, see your Ruud Parts and Accessories Catalog, call **800.621.5622** or go to www.ruudparts.com.

LIMITED WARRANTY

See Ruud Warranty Certificate for complete information.

†LEED points may apply for specific products. See product spec sheet for details. Uniform Energy Factor based on Department of Energy (DOE) requirements.

In keeping with its policy of continuous progress and product improvement, Ruud reserves the right to make changes without notice.

In keeping with its policy of continuous progress and product improvement, Ruud reserves the right to make changes without notice.

Ruud Water Heating
 1115 Northmeadow Parkway, Suite 100
 Roswell, Georgia 30076



PRINTED IN U.S.A. 08/24 WP FORM NO. 101R-95 Rev. 38